

Reference Document

P/N 20004383, Rev. BB
December 2012

**Micro Motion[®]
PED Tagging Information**

This reference document covers information tagged on Micro Motion meters that comply with the Pressure Equipment Directive.

PED Certificate Holder Micro Motion Inc., Boulder, CO
 Temperature Ratings Refer to ATEX Installation Manual at www.micromotion.com/atex
 PED Notified Body Number 0036
 Fluid Group I

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF200A312 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; EN 1092-1 Form D	28.5
CMF200A316 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; EN 1092-1 Form D	28.5
CMF200A341 *** (N, V, Z or 6) ****	1½-inch ANSI CL150 weld neck raised face flange	8.4
CMF200A342 *** (N, V, Z or 6) ****	1½-inch ANSI CL300 weld neck raised face flange	30.3
CMF200A343 *** (N, V, Z or 6) ****	1½-inch ANSI CL600 weld neck raised face flange	60.7
CMF200A363 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMF200A365 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMF200A366 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; EN 1092-1 Form D	71.4
CMF200A367 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; EN 1092-1 Form D	71.4
CMF200A368 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; EN 1092-1 Form B1	28.5
CMF200A369 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; EN 1092-1 Form B1	28.5
CMF200A377 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF200A378 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF200A379 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF200A380 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF200A381 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF200A382 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF200A383 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF200A384 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF200A418 *** (N, V, Z or 6) ****	2-inch ANSI CL150 weld neck raised face flange	8.4
CMF200A419 *** (N, V, Z or 6) ****	2-inch ANSI CL300 weld neck raised face flange	30.3
CMF200A420 *** (N, V, Z or 6) ****	2-inch ANSI CL600 weld neck raised face flange	60.7
CMF200B540 *** (N, V, Z or 6) ****	1½-inch ANSI CL150 lap joint flange	8.4

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF200B541 *** (N, V, Z or 6) ****	1½-inch ANSI CL300 lap joint flange	29.5
CMF200B543 *** (N, V, Z or 6) ****	DN40 PN40 lap joint flange; DIN 2656 type C face	23.0
CMF200B544 *** (N, V, Z or 6) ****	2-inch ANSI CL150 lap joint flange	8.4
CMF200B545 *** (N, V, Z or 6) ****	2-inch ANSI CL300 lap joint flange	29.5
CMF200B547 *** (N, V, Z or 6) ****	DN50 PN40 lap joint flange; DIN 2656 type C face	23.0
CMF200B548 *** (N, V, Z or 6) ****	DN40 PN40 lap joint flange; EN 1092-1 Form B1	23.0
CMF200B549 *** (N, V, Z or 6) ****	DN50 PN40 lap joint flange; EN 1092-1 Form B1	23.0
CMF200H540 *** (N, V, Z or 6) ****	1½-inch ANSI CL150 lap joint flange	13.1
CMF200H541 *** (N, V, Z or 6) ****	1½-inch ANSI CL300 lap joint flange	34.1
CMF200H543 *** (N, V, Z or 6) ****	DN40 PN40 lap joint flange; DIN 2656 type C face	27.8
CMF200H544 *** (N, V, Z or 6) ****	2-inch ANSI CL150 lap joint flange	13.1
CMF200H545 *** (N, V, Z or 6) ****	2-inch ANSI CL300 lap joint flange	34.1
CMF200H547 *** (N, V, Z or 6) ****	DN50 PN40 lap joint flange; DIN 2656 type C face	27.8
CMF200H548 *** (N, V, Z or 6) ****	DN40 PN40 lap joint flange; EN 1092-1 Form B1	27.8
CMF200H549 *** (N, V, Z or 6) ****	DN50 PN40 lap joint flange; EN 1092-1 Form B1	27.8
CMF200L441 *** (N, V, Z or 6) ****	1½-inch ANSI CL150 weld neck raised face flange	13.1
CMF200L442 *** (N, V, Z or 6) ****	1½-inch ANSI CL300 weld neck raised face flange	34.1
CMF200L457 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; EN 1092-1 Form B1	27.8
CMF200L458 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; EN 1092-1 Form B1	27.8
CMF200L481 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; DIN 2526 type C face	27.8
CMF200L482 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; DIN 2526 type C face	27.8
CMF200L518 *** (N, V, Z or 6) ****	2-inch ANSI CL150 weld neck raised face flange	13.1
CMF200L519 *** (N, V, Z or 6) ****	2-inch ANSI CL300 weld neck raised face flange	34.1
CMF200M312 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF200M316 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF200M341 *** (N, V, Z or 6) ****	1½-inch ANSI CL150 weld neck raised face flange	13.6
CMF200M342 *** (N, V, Z or 6) ****	1½-inch ANSI CL300 weld neck raised face flange	35.5
CMF200M343 *** (N, V, Z or 6) ****	1½-inch ANSI CL600 weld neck raised face flange	70.9
CMF200M351 *** (N, V, Z or 6) ****	1½-inch sanitary fitting (Tri-Clamp compatible)	64.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF200M352 *** (N, V, Z or 6) ****	2-inch sanitary fitting (Tri-Clamp compatible)	64.5
CMF200M363 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF200M365 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF200M366 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF200M367 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF200M368 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF200M369 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF200M377 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; DIN 2637 type E face 100	83.8
CMF200M378 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; DIN 2637 type E face 100	83.8
CMF200M379 *** (N, V, Z or 6) ****	DN40 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF200M380 *** (N, V, Z or 6) ****	DN50 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF200M381 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF200M382 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF200M383 *** (N, V, Z or 6) ****	DN40 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF200M384 *** (N, V, Z or 6) ****	DN50 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF200M418 *** (N, V, Z or 6) ****	2-inch ANSI CL150 weld neck raised face flange	13.6
CMF200M419 *** (N, V, Z or 6) ****	2-inch ANSI CL300 weld neck raised face flange	35.5
CMF200M420 *** (N, V, Z or 6) ****	2-inch ANSI CL600 weld neck raised face flange	70.9
CMF300A326 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMF300A333 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form D	28.5
CMF300A355 *** (N, V, Z or 6) ****	3-inch ANSI CL150 weld neck raised face flange	8.4
CMF300A356 *** (N, V, Z or 6) ****	3-inch ANSI CL300 weld neck raised face flange	30.3
CMF300A357 *** (N, V, Z or 6) ****	3-inch ANSI CL600 weld neck raised face flange	60.7
CMF300A358 *** (N, V, Z or 6) ****	3-inch ANSI CL900 weld neck raised face flange	91.0
CMF300A359 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form D	71.4
CMF300A371 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMF300A372 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMF300A373 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMF300A374 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	71.4

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF300A375 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; EN 1092-1 Form D	71.4
CMF300A391 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF300A392 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF300A393 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF300A394 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF300A395 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF300A396 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF300A397 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF300A398 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF300A425 *** (N, V, Z or 6) ****	4-inch ANSI CL150 weld neck raised face flange	8.4
CMF300A426 *** (N, V, Z or 6) ****	4-inch ANSI CL300 weld neck raised face flange	30.3
CMF300A427 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	60.7
CMF300A428 *** (N, V, Z or 6) ****	4-inch ANSI CL900 weld neck raised face flange	91.0
CMF300B550 *** (N, V, Z or 6) ****	3-inch ANSI CL150 lap joint flange	8.4
CMF300B551 *** (N, V, Z or 6) ****	3-inch ANSI CL300 lap joint flange	29.5
CMF300B553 *** (N, V, Z or 6) ****	DN80 PN40 lap joint flange; DIN 2656 type C face	23.0
CMF300B554 *** (N, V, Z or 6) ****	DN80 PN40 lap joint flange; EN 1092-1 Form B1	23.0
CMF300H550 *** (N, V, Z or 6) ****	3-inch ANSI CL150 lap joint flange	13.1
CMF300H551 *** (N, V, Z or 6) ****	3-inch ANSI CL300 lap joint flange	34.1
CMF300H553 *** (N, V, Z or 6) ****	DN80 PN40 lap joint flange; DIN 2656 type C face	27.8
CMF300H554 *** (N, V, Z or 6) ****	DN80 PN40 lap joint flange; EN 1092-1 Form B1	27.8
CMF300L455 *** (N, V, Z or 6) ****	3-inch ANSI CL150 weld neck raised face flange	13.1
CMF300L456 *** (N, V, Z or 6) ****	3-inch ANSI CL300 weld neck raised face flange	34.1
CMF300L459 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; EN 1092-1 Form B1	27.8
CMF300L491 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; DIN 2526 type C face	27.8
CMF300M326 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF300M333 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF300M355 *** (N, V, Z or 6) ****	3-inch ANSI CL150 weld neck raised face flange	13.6
CMF300M356 *** (N, V, Z or 6) ****	3-inch ANSI CL300 weld neck raised face flange	35.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF300M357 *** (N, V, Z or 6) ****	3-inch ANSI CL600 weld neck raised face flange	70.9
CMF300M359 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF300M361 *** (N, V, Z or 6) ****	3-inch sanitary fitting (Tri-Clamp compatible)	64.5
CMF300M371 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF300M372 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF300M373 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF300M374 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF300M375 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange EN 1092-1 Form D	83.8
CMF300M391 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF300M392 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF300M393 *** (N, V, Z or 6) ****	DN80 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF300M394 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF300M395 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; DIN 2637 type E face	83.8
CMF300M396 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type E face	83.8
CMF300M397 *** (N, V, Z or 6) ****	DN80 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF300M398 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF300M425 *** (N, V, Z or 6) ****	4-inch ANSI CL150 weld neck raised face flange	13.6
CMF300M426 *** (N, V, Z or 6) ****	4-inch ANSI CL300 weld neck raised face flange	35.5
CMF300M427 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	70.9
CMF400A435 *** (N, V, Z or 6) ****	4-inch ANSI CL150 weld neck raised face flange	8.4
CMF400A436 *** (N, V, Z or 6) ****	4-inch ANSI CL300 weld neck raised face flange	30.3
CMF400A437 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	60.7
CMF400A438 *** (N, V, Z or 6) ****	4-inch ANSI CL900 weld neck raised face flange	85.5
CMF400A443 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMF400A444 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMF400A445 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMF400A446 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMF400A447 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form D	71.4
CMF400A448 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form D	71.4

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF400A451 *** (N, V, Z or 6) ****	6-inch ANSI CL150 weld neck raised face flange	8.4
CMF400A452 *** (N, V, Z or 6) ****	6-inch ANSI CL300 weld neck raised face flange	30.3
CMF400A453 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	60.7
CMF400A460 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF400A461 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; DIN 2635 type C face	28.5
CMF400A462 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF400A463 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; DIN 2635 type N grooved face	28.5
CMF400A464 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF400A465 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; DIN 2637 type E face	71.4
CMF400A466 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF400A467 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; DIN 2637 type N grooved face	71.4
CMF400A478 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form D	28.5
CMF400A480 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form D	28.5
CMF400B906 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMF400B907 *** (N, V, Z or 6) ****	4-inch ANSI CL150 lap joint flange	8.4
CMF400B908 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMF400B910 *** (N, V, Z or 6) ****	DN100 PN160 weld neck flange; EN 1092-1 Form B3	100.0
CMF400B911 *** (N, V, Z or 6) ****	4-inch ANSI CL150 lap joint flange	8.4
CMF400B912 *** (N, V, Z or 6) ****	4-inch ANSI CL300 lap joint flange	40.2
CMF400B913 *** (N, V, Z or 6) ****	4-inch ANSI CL600 lap joint flange	80.3
CMF400B914 *** (N, V, Z or 6) ****	4-inch ANSI CL900 lap joint flange	120.5
CMF400H906 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMF400H907 *** (N, V, Z or 6) ****	4-inch ANSI CL150 lap joint flange	13.1
CMF400H908 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMF400H910 *** (N, V, Z or 6) ****	DN100 PN160 weld neck flange; EN 1092-1 Form B2	160.0
CMF400H911 *** (N, V, Z or 6) ****	4-inch ANSI CL150 weld neck raised face flange	13.8
CMF400H912 *** (N, V, Z or 6) ****	4-inch ANSI CL300 weld neck raised face flange	48.3
CMF400H913 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	96.2
CMF400H914 *** (N, V, Z or 6) ****	4-inch ANSI CL900 weld neck raised face flange	144.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF400M435 *** (N, V, Z or 6) ****	4-inch ANSI CL150 weld neck raised face flange	13.6
CMF400M436 *** (N, V, Z or 6) ****	4-inch ANSI CL300 weld neck raised face flange	35.5
CMF400M437 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	70.9
CMF400M443 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF400M444 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMF400M445 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF400M446 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF400M447 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF400M448 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF400M451 *** (N, V, Z or 6) ****	6-inch ANSI CL150 weld neck raised face flange	13.6
CMF400M452 *** (N, V, Z or 6) ****	6-inch ANSI CL300 weld neck raised face flange	35.5
CMF400M453 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	70.9
CMF400M460 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF400M461 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; DIN 2635 type C face	33.5
CMF400M462 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF400M463 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
CMF400M464 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type E face	83.8
CMF400M465 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; DIN 2637 type E face	83.8
CMF400M466 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF400M467 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
CMF400M478 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF400M480 *** (N, V, Z or 6) ****	DN100 PN40 weld neck flange; EN 1092-1 Form D	33.5
CMF400P437 *** (N, V, Z or 6) ****	4-inch ANSI CL600 weld neck raised face flange	70.9
CMF400P438 *** (N, V, Z or 6) ****	4-inch ANSI CL900 weld neck raised face flange	106.4
CMF400P439 *** (N, V, Z or 6) ****	4-inch ANSI CL1500 weld neck raised face flange	177.3
CMF400P445 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF400P446 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMF400P447 *** (N, V, Z or 6) ****	DN100 PN100 weld neck flange; EN 1092-1 Form D	83.8
CMF400P448 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form D	83.8

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMF400P453 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	70.9
CMF400P468 *** (N, V, Z or 6) ****	DN100 PN160 weld neck flange; EN 1092-1 Form B2	134.1
CMF400P562 *** (N, V, Z or 6) ****	4-inch ANSI CL600 carbon steel/316L stainless steel lap joint flange	87.2
CMF400P563 *** (N, V, Z or 6) ****	4-inch ANSI CL900 carbon steel/316L stainless steel lap joint flange	131.0
CMFHC2A451 *** (N, V, Z or 6) ****	6-inch ANSI CL150 weld neck raised face flange	8.4
CMFHC2A452 *** (N, V, Z or 6) ****	6-inch ANSI CL300 weld neck raised face flange	30.3
CMFHC2A453 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	60.7
CMFHC2A801 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMFHC2A802 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMFHC2A803 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	84.3
CMFHC2A810 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	8.4
CMFHC2A811 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	30.3
CMFHC2A818 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	60.7
CMFHC2A819 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	84.3
CMFHC2A821 *** (N, V, Z or 6) ****	6-inch ANSI CL900 weld neck raised face flange	84.3
CMFHC2A822 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMFHC2A823 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMFHC2A824 *** (N, V, Z or 6) ****	DN150 PN160 weld neck flange; EN 1092-1 Form B2	84.3
CMFHC2M451 *** (N, V, Z or 6) ****	6-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC2M452 *** (N, V, Z or 6) ****	6-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC2M453 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC2M801 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC2M802 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC2M803 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	98.5
CMFHC2M810 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC2M811 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC2M818 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC2M819 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	98.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMFHC2M821 *** (N, V, Z or 6) ****	6-inch ANSI CL900 weld neck raised face flange	98.5
CMFHC2M822 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC2M823 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC2M824 *** (N, V, Z or 6) ****	DN150 PN160 weld neck flange; EN 1092-1 Form B2	98.5
CMFHC2Y956 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMFHC2Y957 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMFHC2Y958 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	132.3
CMFHC2Y959 *** (N, V, Z or 6) ****	DN150 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMFHC2Y960 *** (N, V, Z or 6) ****	DN150 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMFHC2Y961 *** (N, V, Z or 6) ****	DN150 PN160 weld neck flange; EN 1092-1 Form B2	132.3
CMFHC2Y962 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	14.0
CMFHC2Y963 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	42.7
CMFHC2Y964 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	85.4
CMFHC2Y965 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	128.1
CMFHC2Y966 *** (N, V, Z or 6) ****	6-inch ANSI CL150 weld neck raised face flange	14.0
CMFHC2Y967 *** (N, V, Z or 6) ****	6-inch ANSI CL300 weld neck raised face flange	42.7
CMFHC2Y968 *** (N, V, Z or 6) ****	6-inch ANSI CL600 weld neck raised face flange	85.4
CMFHC2Y969 *** (N, V, Z or 6) ****	6-inch ANSI CL900 weld neck raised face flange	128.1
CMFHC3A801 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMFHC3A802 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMFHC3A803 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	84.3
CMFHC3A804 *** (N, V, Z or 6) ****	DN250 PN40 weld neck flange; EN 1092-1 Form B1	28.5
CMFHC3A805 *** (N, V, Z or 6) ****	DN250 PN100 weld neck flange; EN 1092-1 Form B2	71.4
CMFHC3A806 *** (N, V, Z or 6) ****	DN250 PN160 weld neck flange; EN 1092-1 Form B2	84.3
CMFHC3A810 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	8.4
CMFHC3A811 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	30.3
CMFHC3A812 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	75.1
CMFHC3A813 *** (N, V, Z or 6) ****	10-inch ANSI CL150 weld neck raised face flange	8.4
CMFHC3A814 *** (N, V, Z or 6) ****	10-inch ANSI CL300 weld neck raised face flange	30.3

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMFHC3A815 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	60.7
CMFHC3A816 *** (N, V, Z or 6) ****	10-inch ANSI CL600 lap joint flange	75.1
CMFHC3A817 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	60.7
CMFHC3A818 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	60.7
CMFHC3A819 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	84.3
CMFHC3A820 *** (N, V, Z or 6) ****	10-inch ANSI CL900 weld neck raised face flange	84.3
CMFHC3M801 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC3M802 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC3M803 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	98.5
CMFHC3M804 *** (N, V, Z or 6) ****	DN250 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC3M805 *** (N, V, Z or 6) ****	DN250 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC3M806 *** (N, V, Z or 6) ****	DN250 PN160 weld neck flange; EN 1092-1 Form B2	98.5
CMFHC3M810 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC3M811 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC3M812 *** (N, V, Z or 6) ****	8-inch ANSI CL600 lap joint flange	87.2
CMFHC3M813 *** (N, V, Z or 6) ****	10-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC3M814 *** (N, V, Z or 6) ****	10-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC3M815 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC3M816 *** (N, V, Z or 6) ****	10-inch ANSI CL600 lap joint flange	87.2
CMFHC3M817 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC3M818 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC3M819 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	98.5
CMFHC3M820 *** (N, V, Z or 6) ****	10-inch ANSI CL900 weld neck raised face flange	98.5
CMFHC3Y825 *** (N, V, Z or 6) ****	DN200 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMFHC3Y826 *** (N, V, Z or 6) ****	DN200 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMFHC3Y827 *** (N, V, Z or 6) ****	DN200 PN160 weld neck flange; EN 1092-1 Form B2	132.3
CMFHC3Y828 *** (N, V, Z or 6) ****	DN250 PN40 weld neck flange; EN 1092-1 Form B1	40.0
CMFHC3Y829 *** (N, V, Z or 6) ****	DN250 PN100 weld neck flange; EN 1092-1 Form B2	100.0
CMFHC3Y830 *** (N, V, Z or 6) ****	DN250 PN160 weld neck flange; EN 1092-1 Form B2	132.3

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
CMFHC3Y831 *** (N, V, Z or 6) ****	8-inch ANSI CL150 weld neck raised face flange	14.0
CMFHC3Y832 *** (N, V, Z or 6) ****	8-inch ANSI CL300 weld neck raised face flange	42.7
CMFHC3Y833 *** (N, V, Z or 6) ****	8-inch ANSI CL600 weld neck raised face flange	85.4
CMFHC3Y834 *** (N, V, Z or 6) ****	8-inch ANSI CL900 weld neck raised face flange	128.1
CMFHC3Y836 *** (N, V, Z or 6) ****	10-inch ANSI CL150 weld neck raised face flange	14.0
CMFHC3Y837 *** (N, V, Z or 6) ****	10-inch ANSI CL300 weld neck raised face flange	42.7
CMFHC3Y838 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	85.4
CMFHC3Y839 *** (N, V, Z or 6) ****	10-inch ANSI CL900 weld neck raised face flange	128.1
CMFHC4M841 *** (N, V, Z or 6) ****	10-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC4M842 *** (N, V, Z or 6) ****	10-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC4M843 *** (N, V, Z or 6) ****	10-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC4M844 *** (N, V, Z or 6) ****	10-inch ANSI CL900 weld neck raised face flange	98.4
CMFHC4M845 *** (N, V, Z or 6) ****	12-inch ANSI CL150 weld neck raised face flange	13.6
CMFHC4M846 *** (N, V, Z or 6) ****	12-inch ANSI CL300 weld neck raised face flange	35.5
CMFHC4M847 *** (N, V, Z or 6) ****	12-inch ANSI CL600 weld neck raised face flange	70.9
CMFHC4M848 *** (N, V, Z or 6) ****	12-inch ANSI CL900 weld neck raised face flange	98.4
CMFHC4M849 *** (N, V, Z or 6) ****	DN250 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC4M850 *** (N, V, Z or 6) ****	DN250 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC4M851 *** (N, V, Z or 6) ****	DN250 PN160 weld neck flange; EN 1092-1 Form B2	98.4
CMFHC4M852 *** (N, V, Z or 6) ****	DN300 PN40 weld neck flange; EN 1092-1 Form B1	33.5
CMFHC4M853 *** (N, V, Z or 6) ****	DN300 PN100 weld neck flange; EN 1092-1 Form B2	83.8
CMFHC4M854 *** (N, V, Z or 6) ****	DN300 PN160 weld neck flange; EN 1092-1 Form B2	98.4
DH150S154 *(N or B)	1½-inch high-pressure clamp-type flange; Size 14 seal ring	64.5
DH150S932 *(N or B)	DN40 PN160 weld neck flange; DIN 2638 type E face	134.1
DH150S933 *(N or B)	DN40 PN250 weld neck raised face flange; DIN 2628 type E face	209.6
DH150S934 *(N or B)	DN40 PN320 weld neck raised face flange; DIN 2629 type E face	268.3
DH150S935 *(N or B)	DN40 PN400 weld neck raised face flange; DIN 2627 type E face	out
DH150S936 *(N or B)	1½-inch ANSI 900/CL1500 weld neck raised face	177.3
DH150S938 *(N or B)	1½-inch ANSI CL2500 weld neck raised face flange	295.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
DH300S156 *(N or B)	3-inch ANSI CL300 weld neck raised face flange	35.5
DH300S157 *(N or B)	3-inch ANSI CL600 weld neck raised face flange	70.9
DH300S164 *(N or B)	4-inch high-pressure clamp-type flange; size 27 seal ring	201.6
DH300S246 *(N or B)	3-inch ANSI CL900 weld neck raised face flange	106.4
DH300S942 *(N or B)	DN80 PN100 weld neck flange; DIN 2637 type E face	83.8
DH300S943 *(N or B)	DN80 PN160 weld neck flange; DIN 2638 type E face	134.1
DH300S944 *(N or B)	DN80 PN250 weld neck raised face flange; DIN 2628 type E face	201.6
DH300S946 *(N or B)	3-inch ANSI CL1500 weld neck raised face flange	177.3
DH300S947 *(N or B)	3-inch ANSI CL2500 weld neck raised face flange	201.6
DL200S226 *(N or B)	2-inch sanitary fitting (Tri-Clamp compatible)	48.0
DL200S227 *(N or B)	2-inch ANSI CL150 lap joint flange	13.1
DL200S228 *(N or B)	2-inch ANSI CL300 lap joint flange	34.1
DL200S954 *(N or B)	DN50 DIN11851 aseptic coupling	20.9
DL200S955 *(N or B)	DN50 PN40 lap joint flange; 2656 type C face	27.8
DS150Z141 *(N or B)	1½-inch ANSI CL150 weld neck raised face flange	15.5
DS150Z142 *(N or B)	1½-inch ANSI CL300 weld neck raised face flange	40.4
DS150Z143 *(N or B)	1½-inch ANSI CL600 weld neck raised face flange	51.0
DS150Z144 *(N or B)	DN40 PN40 weld neck flange; DIN 2635 type C face	38.2
DS150Z218 *(N or B)	2-inch ANSI CL150 weld neck raised face flange	15.5
DS300H203 *(N or B)	3-inch ANSI CL150 lap joint flange	13.1
DS300H204 *(N or B)	3-inch ANSI CL300 lap joint flange	34.1
DS300H211 *(N or B)	DN80 PN40 lap joint flange; DIN 2656 type C face	27.8
DS300H949 *(N or B)	3-inch ANSI CL600 lap joint flange	48.5
DS300S155 *(N or B)	3-inch ANSI CL150 weld neck raised face flange	13.6
DS300S156 *(N or B)	3-inch ANSI CL300 weld neck raised face flange	35.5
DS300S157 *(N or B)	3-inch ANSI CL600 weld neck raised face flange	48.0
DS300S158 *(N or B)	DN80 PN40 weld neck flange; DIN 2635 type C face	33.5
DS300S161 *(N or B)	3-inch sanitary fitting (Tri-Clamp compatible)	48.0
DS300S941 *(N or B)	DN80 PN64 weld neck flange; DIN 2636 type E face	48.0

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
DS300Z155 *(N or B)	3-inch ANSI CL150 weld neck raised face flange	15.5
DS300Z156 *(N or B)	3-inch ANSI CL300 weld neck raised face flange	40.4
DS300Z158 *(N or B)	DN80 PN40 weld neck flange; DIN 2635 type C face	38.2
F200H537 *** (N, V or Z) *****	1½-inch ANSI CL600 lap joint flange	68.6
F200H540 *** (N, V or Z) *****	1½-inch ANSI CL150 lap joint flange	13.1
F200H541 *** (N, V or Z) *****	1½-inch ANSI CL300 lap joint flange	34.1
F200H544 *** (N, V or Z) *****	2-inch ANSI CL150 lap joint flange	13.1
F200H545 *** (N, V or Z) *****	2-inch ANSI CL300 lap joint flange	34.1
F200H548 *** (N, V or Z) *****	DN40 PN40 lap joint flange; EN 1092-1 Form B1	27.8
F200H549 *** (N, V or Z) *****	DN50 PN40 lap joint flange; EN 1092-1 Form B1	27.8
F200S312 *** (N, V or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form D	33.5
F200S316 *** (N, V or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form D	33.5
F200S341 *** (N, V or Z) *****	1½-inch ANSI CL150 weld neck raised face flange	13.6
F200S342 *** (N, V or Z) *****	1½-inch ANSI CL300 weld neck raised face flange	35.5
F200S343 *** (N, V or Z) *****	1½-inch ANSI CL600 weld neck raised face flange	70.9
F200S351 *** (N, V or Z) *****	1½-inch sanitary fitting (Tri-Clamp compatible)	64.5
F200S352 *** (N, V or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	64.5
F200S353 *** (N, V or Z) *****	40mm DIN11851 aseptic coupling	33.5
F200S354 *** (N, V or Z) *****	50mm DIN11851 aseptic coupling	20.9
F200S363 *** (N, V or Z) *****	DN40 PN100 weld neck flange; EN 1092-1 Form B2	83.8
F200S365 *** (N, V or Z) *****	DN50 PN100 weld neck flange; EN 1092-1 Form B2	83.8
F200S366 *** (N, V or Z) *****	DN40 PN100 weld neck flange; EN 1092-1 Form D	83.8
F200S367 *** (N, V or Z) *****	DN50 PN100 weld neck flange; EN 1092-1 Form D	83.8
F200S368 *** (N, V or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form B1	33.5
F200S369 *** (N, V or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form B1	33.5
F200S376 *** (N, V or Z) *****	DN50 PN160 weld neck flange; DIN 2638 type E face	103.7
F200S378 *** (N, V or Z) *****	DN50 PN100 weld neck flange; DIN 2637 type E face	83.8
F200S381 *** (N, V or Z) *****	DN40 PN40 weld neck flange; DIN 2635 type C face	33.5
F200S382 *** (N, V or Z) *****	DN50 PN40 weld neck flange; DIN 2635 type C face	33.5

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
F200S418 *** (N, V or Z) *****	2-inch ANSI CL150 weld neck raised face flange	13.6
F200S419 *** (N, V or Z) *****	2-inch ANSI CL300 weld neck raised face flange	35.5
F200S420 *** (N, V or Z) *****	2-inch ANSI CL600 weld neck raised face flange	70.9
F300H539 *** (N, V or Z) *****	3-inch ANSI CL600 lap joint flange	68.6
F300H550 *** (N, V or Z) *****	3-inch ANSI CL150 lap joint flange	13.1
F300H551 *** (N, V or Z) *****	3-inch ANSI CL300 lap joint flange	34.1
F300H554 *** (N, V or Z) *****	DN80 PN40 lap joint flange; EN 1092-1 Form B1	27.8
F300S326 *** (N, V or Z) *****	DN80 PN40 weld neck flange; EN 1092-1 Form D	33.5
F300S333 *** (N, V or Z) *****	DN100 PN40 weld neck flange; EN 1092-1 Form D	33.5
F300S355 *** (N, V or Z) *****	3-inch ANSI CL150 weld neck raised face flange	13.6
F300S356 *** (N, V or Z) *****	3-inch ANSI CL300 weld neck raised face flange	35.5
F300S357 *** (N, V or Z) *****	3-inch ANSI CL600 weld neck raised face flange	70.9
F300S359 *** (N, V or Z) *****	DN100 PN100 weld neck flange; EN 1092-1 Form D	83.8
F300S361 *** (N, V or Z) *****	3-inch sanitary fitting (Tri-Clamp compatible)	64.5
F300S371 *** (N, V or Z) *****	DN80 PN40 weld neck flange; EN 1092-1 Form B1	33.5
F300S372 *** (N, V or Z) *****	DN100 PN40 weld neck flange; EN 1092-1 Form B1	33.5
F300S373 *** (N, V or Z) *****	DN80 PN100 weld neck flange; EN 1092-1 Form B2	83.8
F300S374 *** (N, V or Z) *****	DN100 PN100 weld neck flange; EN 1092-1 Form B2	83.8
F300S375 *** (N, V or Z) *****	DN80 PN100 weld neck flange; EN 1092-1 Form D	83.8
F300S391 *** (N, V or Z) *****	DN80 PN40 weld neck flange; DIN 2635 type C face	33.5
F300S392 *** (N, V or Z) *****	DN100 PN40 weld neck flange; DIN 2635 type C face	33.5
F300S393 *** (N, V or Z) *****	DN80 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
F300S394 *** (N, V or Z) *****	DN100 PN40 weld neck flange; DIN 2635 type N grooved face	33.5
F300S395 *** (N, V or Z) *****	DN80 PN100 weld neck flange; DIN 2637 type E face	83.8
F300S396 *** (N, V or Z) *****	DN100 PN100 weld neck flange; DIN 2637 type E face	83.8
F300S397 *** (N, V or Z) *****	DN80 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
F300S398 *** (N, V or Z) *****	DN100 PN100 weld neck flange; DIN 2637 type N grooved face	83.8
F300S410 *** (N, V or Z) *****	3-inch Victaulic compatible fitting	48.3
F300S425 *** (N, V or Z) *****	4-inch ANSI CL150 weld neck raised face flange	13.6

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
F300S426 *** (N, V or Z) *****	4-inch ANSI CL300 weld neck raised face flange	35.5
F300S427 *** (N, V or Z) *****	4-inch ANSI CL600 weld neck raised face flange	70.9
H200F352 *** (N, V or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	64.5
H200F354 *** (N, V or Z) *****	DN50 DIN11851 aseptic coupling	20.9
H200F669 *** (N, V or Z) *****	2s IDF Type CLF2-W aseptic fitting	9.1
H200F678 *** (N, V or Z) *****	DN50 DIN11864-1A aseptic coupling	20.9
H200S352 *** (N, V or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	64.5
H200S354 *** (N, V or Z) *****	50mm DIN11851 aseptic coupling	20.9
H200S669 *** (N, V or Z) *****	2s IDF Type CLF2-W aseptic fitting	9.1
H200S678 *** (N, V or Z) *****	50mm DIN11864-1A aseptic coupling	20.9
H300F361 *** (N, V or Z) *****	3-inch sanitary fitting (Tri-Clamp compatible)	64.5
H300F664 *** (N, V or Z) *****	DN76.1 IDF (ISO2853) aseptic coupling	9.1
H300F679 *** (N, V or Z) *****	DN80 DIN11864-1A aseptic coupling	20.9
H300F680 *** (N, V or Z) *****	DN80 DIN11864-2A aseptic coupling	13.3
H300F685 *** (N, V or Z) *****	DN80 DIN11851 aseptic coupling	20.9
H300F687 *** (N, V or Z) *****	3s IDF Type CLF2-W aseptic fitting	9.1
H300F694 *** (N, V or Z) *****	DN76 SMS 1145 aseptic coupling	5.1
H300S361 *** (N, V or Z) *****	3-inch sanitary fitting (Tri-Clamp compatible)	64.5
H300S664 *** (N, V or Z) *****	DN76.1 IDF (ISO2853) aseptic coupling	9.1
H300S679 *** (N, V or Z) *****	DN80 DIN11864-1A aseptic coupling	20.9
H300S680 *** (N, V or Z) *****	DN80 DIN11864-2A aseptic flange	13.3
H300S685 *** (N, V or Z) *****	DN80 DIN11851 aseptic coupling	20.9
H300S687 *** (N, V or Z) *****	3s IDF Type CLF2-W aseptic fitting	9.1
H300S694 *** (N, V or Z) *****	DN76 SMS 1145 aseptic coupling	5.1
R200S312 *** (N or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form D	33.5
R200S316 *** (N or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form D	33.5
R200S341 *** (N or Z) *****	1½-inch ANSI CL150 weld neck raised face flange	13.6
R200S342 *** (N or Z) *****	1½-inch ANSI CL300 weld neck raised face flange	35.5
R200S343 *** (N or Z) *****	1½-inch ANSI CL600 weld neck raised face flange	70.9

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
R200S351 *** (N or Z) *****	1½-inch sanitary fitting (Tri-Clamp compatible)	64.5
R200S352 *** (N or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	64.5
R200S353 *** (N or Z) *****	40mm DIN11851 aseptic coupling	33.5
R200S354 *** (N or Z) *****	50mm DIN11851 aseptic coupling	20.9
R200S363 *** (N or Z) *****	DN40 PN100 weld neck flange; EN 1092-1 Form B2	83.8
R200S365 *** (N or Z) *****	DN50 PN100 weld neck flange; EN 1092-1 Form B2	83.8
R200S366 *** (N or Z) *****	DN40 PN100 weld neck flange; EN 1092-1 Form D	83.8
R200S367 *** (N or Z) *****	DN50 PN100 weld neck flange; EN 1092-1 Form D	83.8
R200S368 *** (N or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form B1	33.5
R200S369 *** (N or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form B1	33.5
R200S376 *** (N or Z) *****	DN50 PN160 weld neck flange; DIN 2638 type E face	103.7
R200S378 *** (N or Z) *****	DN50 PN100 weld neck flange; DIN 2637 type E face	83.8
R200S381 *** (N or Z) *****	DN40 PN40 weld neck flange; DIN 2635 type C face	33.5
R200S382 *** (N or Z) *****	DN50 PN40 weld neck flange; DIN 2635 type C face	33.5
R200S418 *** (N or Z) *****	2-inch ANSI CL150 weld neck raised face flange	13.6
R200S419 *** (N or Z) *****	2-inch ANSI CL300 weld neck raised face flange	35.5
R200S420 *** (N or Z) *****	2-inch ANSI CL600 weld neck raised face flange	70.9
T150F624 *** (N, V or Z) *****	1½-inch sanitary fitting (Tri-Clamp compatible)	66.9
T150F625 *** (N, V or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	66.9
T150F641 *** (N, V or Z) *****	1½-inch ANSI CL150 socket weld raised face flange	14.8
T150F642 *** (N, V or Z) *****	1½-inch ANSI CL300 socket weld raised face flange	38.6
T150F643 *** (N, V or Z) *****	1½-inch ANSI CL600 socket weld raised face flange	77.2
T150F644 *** (N, V or Z) *****	2-inch ANSI CL150 socket weld raised face flange	14.8
T150F645 *** (N, V or Z) *****	2-inch ANSI CL300 socket weld raised face flange	38.6
T150F646 *** (N, V or Z) *****	2-inch ANSI CL600 socket weld raised face flange	77.2
T150F652 *** (N, V or Z) *****	DN40 PN40 socket weld flange; DIN 2512 type N grooved face	36.4
T150F653 *** (N, V or Z) *****	DN50 PN40 socket weld flange; DIN 2512 type N grooved face	36.4
T150F663 *** (N, V or Z) *****	DN51 IDF (ISO2853) aseptic coupling	9.5
T150F673 *** (N, V or Z) *****	DN40 DIN 11851 aseptic coupling	30.9

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
T150F674 *** (N, V or Z) *****	DN50 DIN 11851 aseptic coupling	19.2
T150F678 *** (N, V or Z) *****	DN50 DIN 11864-1A aseptic coupling	19.2
T150F681 *** (N, V or Z) *****	DN40 PN40 socket weld flange; DIN 2526 type C face	36.4
T150F682 *** (N, V or Z) *****	DN40 PN100 socket weld flange; DIN 2526 type E face	91.1
T150F683 *** (N, V or Z) *****	DN50 PN40 socket weld flange; DIN 2526 type C face	36.4
T150F684 *** (N, V or Z) *****	DN50 PN100 socket weld flange; DIN 2526 type E face	91.1
T150F693 *** (N, V or Z) *****	DN51 SMS 1145 aseptic coupling	5.8
T150T624 *** (N, V or Z) *****	1½-inch sanitary fitting (Tri-Clamp compatible)	66.9
T150T625 *** (N, V or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	66.9
T150T641 *** (N, V or Z) *****	1½-inch ANSI CL150 socket weld raised face flange	14.8
T150T642 *** (N, V or Z) *****	1½-inch ANSI CL300 socket weld raised face flange	38.6
T150T643 *** (N, V or Z) *****	1½-inch ANSI CL600 socket weld raised face flange	77.2
T150T644 *** (N, V or Z) *****	2-inch ANSI CL150 socket weld raised face flange	14.8
T150T645 *** (N, V or Z) *****	2-inch ANSI CL300 socket weld raised face flange	38.6
T150T646 *** (N, V or Z) *****	2-inch ANSI CL600 socket weld raised face flange	77.2
T150T652 *** (N, V or Z) *****	DN40 PN40 socket weld flange; DIN 2512 type N grooved face	36.4
T150T653 *** (N, V or Z) *****	DN50 PN40 socket weld flange; DIN 2512 type N grooved face	36.4
T150T656 *** (N, V or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form D	36.4
T150T657 *** (N, V or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form D	36.4
T150T658 *** (N, V or Z) *****	DN40 PN40 weld neck flange; EN 1092-1 Form B1	36.4
T150T659 *** (N, V or Z) *****	DN40 PN100 weld neck flange; EN 1092-1 Form B2	91.1
T150T660 *** (N, V or Z) *****	DN50 PN40 weld neck flange; EN 1092-1 Form B1	36.4
T150T661 *** (N, V or Z) *****	DN50 PN100 weld neck flange; EN 1092-1 Form B2	91.1
T150T663 *** (N, V or Z) *****	DN51 IDF (ISO2853) aseptic coupling	9.5
T150T673 *** (N, V or Z) *****	DN40 DIN 11851 aseptic coupling	30.9
T150T674 *** (N, V or Z) *****	DN50 DIN 11851 aseptic coupling	19.2
T150T678 *** (N, V or Z) *****	DN50 DIN 11864-1A aseptic coupling	19.2
T150T681 *** (N, V or Z) *****	DN40 PN40 socket weld flange; DIN 2526 type C face	36.4
T150T682 *** (N, V or Z) *****	DN40 PN100 socket weld flange; DIN 2526 type E face	91.1

Sensor model (Codes: *** (N, V, Z or 6) ****)	Process connection	Pressure limit at Max Temp PS bar
T150T683 *** (N, V or Z) *****	DN50 PN40 socket weld flange; DIN 2526 type C face	36.4
T150T684 *** (N, V or Z) *****	DN50 PN100 socket weld flange; DIN 2526 type E face	91.1
T150T693 *** (N, V or Z) *****	DN51 SMS 1145 aseptic coupling	5.8
DL200S955 *(N or Z)	DN50 PN40 lap joint flange; 2656 type C face	40
DT150H142 *(N or Z)	1½-inch ANSI CL300 weld neck raised face flange	41
DT150H143 *(N or Z)	1½-inch ANSI CL600 weld neck raised face flange	41
DT150H144 *(N or Z)	DN40 PN40 weld neck flange; DIN 2635 type C face	40
T150* 641 *** (N or Z) *****	1½-inch ANSI CL150 socket weld raised face flange	18
T150* 642 *** (N or Z) *****	1½-inch ANSI CL300 socket weld raised face flange	49
T150* 643 *** (N or Z) *****	1½-inch ANSI CL600 socket weld raised face flange	99
T150* 644 *** (N or Z) *****	2-inch ANSI CL150 socket weld raised face flange	18
T150* 645 *** (N or Z) *****	2-inch ANSI CL300 socket weld raised face flange	49
T150* 646 *** (N or Z) *****	2-inch ANSI CL600 socket weld raised face flange	99
T150* 681 *** (N or Z) *****	DN40 PN40 socket weld flange; DIN 2526 type C face	40
T150* 682 *** (N or Z) *****	DN40 PN100 socket weld flange; DIN 2526 type E face	100
T150* 683 *** (N or Z) *****	DN50 PN40 socket weld flange; DIN 2526 type C face	40
T150* 684 *** (N or Z) *****	DN50 PN100 DIN 2637 socket weld flange; DIN 2526 type E face	100
T150* 652 *** (N or Z) *****	DN40 PN40 socket weld flange; DIN 2512 type N grooved face	40
T150* 653 *** (N or Z) *****	DN50 PN40 socket weld flange; DIN 2512 type N grooved face	40
T150* 624 *** (N or Z) *****	1½-inch sanitary fitting (Tri-Clamp compatible)	10
T150* 625 *** (N or Z) *****	2-inch sanitary fitting (Tri-Clamp compatible)	10
T150* 673 *** (N or Z) *****	DN40 DIN 11851 aseptic coupling	40
T150* 674 *** (N or Z) *****	DN50 DIN 11851 aseptic coupling	25
T150* 693 *** (N or Z) *****	DN51 SMS 1145 aseptic coupling	6
T150* 663 *** (N or Z) *****	DN51 IDF (ISO2853) aseptic coupling	3
T150* 678 *** (N or Z) *****	DN50 DIN 11864-1A aseptic coupling	25

©2012 Micro Motion, Inc. All rights reserved. P/N 20004383, Rev. BB



For the latest Micro Motion product specifications, view the PRODUCTS section of our web site at www.micromotion.com

Micro Motion Inc. USA

Worldwide Headquarters

7070 Winchester Circle
Boulder, Colorado 80301

T +1 303-527-5200

+1 800-522-6277

F +1 303-530-8459

Micro Motion Europe

Emerson Process Management

Neonstraat 1

6718 WX Ede

The Netherlands

T +31 (0) 318 495 555

F +31 (0) 318 495 556

Micro Motion Asia

Emerson Process Management

1 Pandan Crescent

Singapore 128461

Republic of Singapore

T +65 6777-8211

F +65 6770-8003

Micro Motion United Kingdom

Emerson Process Management Limited

Horsfield Way

Bredbury Industrial Estate

Stockport SK6 2SU U.K.

T +44 0870 240 1978

F +44 0800 966 181

Micro Motion Japan

Emerson Process Management

1-2-5, Higashi Shinagawa

Shinagawa-ku

Tokyo 140-0002 Japan

T +81 3 5769-6803

F +81 3 5769-6844

